

SD



GENERAL PURPOSE, FULL FEATURED DVR


The SD offers the user a high performance, easy to use, plug and play DVR designed to suit the needs of small to medium businesses. Each model is preconfigured to work out of the box with minimal set up to help avoid installation and user hassles. The simplified operation is supported by unified local and remote interface, on-screen menus and controls.

FEATURES

- ▶ **8, 12, 16 or 32 video inputs**
- ▶ **Embedded operating system on non-volatile flash memory**
- ▶ **Easily selected recording configurations for 7, 14, 30 or 60 days of storage**
- ▶ **Up to 120pps total**
- ▶ **Storage options up to 1.5 TB HDD**
- ▶ **Built-in CD writer and 3 USB ports**
- ▶ **Auto camera detect and auto record on power-up**
- ▶ **Flexible control options include IR Remote, KBC1, KBC2, USB Keyboard, USB Mouse, or remote client. Optional remote keyboard kit (KBC/ACC)**
- ▶ **NetVu Connected software allows the DVR to operate as a stand-alone unit or as part of a NetVu Connected system**
- ▶ **Digital Video Authentication Capability**
- ▶ **Pan-Tilt-Zoom (PTZ) control using Coaxitron, and most popular protocols**
- ▶ **MultiMode Recording: Dynamically switchable resolution, record rate and compression (MPEG-4 and JPEG) per camera**
- ▶ **TransCoding of video into different formats for efficient remote viewing**
- ▶ **Continuous, scheduled, motion or alarm based recording for each video input**
- ▶ **Analytics Capable (upgrade required)**
- ▶ **Extended Storage accessory via an external SATA connection**
- ▶ **Text support for point of sale data applications**

SPECIFICATION

		SD 8, 12, 16, 32 channel models
	Operating System	Embedded
	Dimensions	(h) 3.5" x (w) 17.3" x (d) 17.5"; [89mm x 440mm x 445mm]
	Operating range	32 F - 104 F (0 C - 40 C); 5% - 85% humidity non-condensing
Video	Weight	25 lbs (11.4kg)
	Video Inputs	8, 12 and 16 with looping; 32 non-looping, BNC
	Operation	NTSC or PAL capable; simultaneous live, record, playback, remote and internet access
	Maximum PPS, total (NTSC)	8 Ch. = 60PPS; 12 ch = 90PPS; 16 and 32 ch = 60 and 120PPS;
	Recording	MPEG-4 and, or JPEG @ QCIF, CIF, 2CIF;
	MultiMode (Recording Algorithms)	Dynamically changes record rates, resolutions and compression setting for each camera
	Trans-Coding	User selectable MPEG-4 and, or JPEG network transmission
	Snapshot/Video Clip	Yes
Audio	Video Outputs	Main (live video resolution = 720 x 448) and Spot
	Audio Line In/Out	1ch bi-directional; Line in: 1Vpk-pk, RCA; Line out: 1V pk-pk, RCA
	Network Audio	Yes
Storage	Local Audio Playback	Real time audio record and playback
	Internal Capacity	8 ch = 250, 500GB; 12 ch = 500, 750GB; 16 ch = 320, 500GB, 1TB; 32 ch = 500GB, 750GB, 1TB, 1.5 TB
	Managed Storage Capability	Single expansion unit via external SATA connection
Alarms	Export Device/Ports	Built-in CD-R and USB (1 front, 2 rear)
	Alarms and Relays	16 normal open/closed tamper proof inputs; keyswitch alarm; 4 relay outputs
	Relay Output Options	Activity or Alarm
	Alarm Log and Reporting	Yes including alarm reporting by email
	Display Alarm on Monitor	Local or Network (via NetVu Observer)
Networking	Simple Activity Detection	Yes
	NIC Interface	10/100
	Network Features	DHCP Capability, File Export, PTZ Control, Bandwidth Management, Remote Administration, Password Protection, FTP Server Support, Built-in Firewall
Other Features	Remote PC Client	NetVu Observer
	Remote Web Browser Client	Programming and administrative only
	POS/ATM Text support	Yes
	PTZ Control	Serial and Coax; Dedicated Micros Serial, JVC, Kalatel, Panasonic WV-CS600/WV-CS850, Pelco C, Pelco D, Philips/Philips 232, Samsung, Sanyo, Sensormatic, Ultrak, Vicon, AD Matrix/AD 168-Matrix, Baxall C, BBV C/RS485/Matrix, Dennard/Dennard C, Emitec, MarkMercer, Vantage, VCL/VCL-Matrix, Vista
	Software upgrade	USB, CD or remotely by computer
	Keyboards	models KBC1 (PTZ button controls) and KBC2 (built-in PTZ joystick)
	Building Controls, Access Integration	via PowerScript software
	Remote Control	IR remote, 2 standard
Video Analytics	Optional	
Mounting	Desktop, Shelf or Rack	
Serial Ports	4 ports for RS232 and RS 485 connections	
Warranty	2 Years	



Example:
SDI2N30

PLEASE CHECK THE WEBSITE OR YOUR LOCAL REPRESENTATIVE FOR PRODUCT ORDERING INFORMATION AND OTHER DEVELOPMENTS



Dedicated Micros USA 14434 Albemarle Point Place, Suite 100, Chantilly, Virginia 20151 USA Toll Free : 800 864-7539
Tel: +1 703 904-7738 Fax: +1 703 904-7743

Dedicated Micros Canada 5580 Explorer Drive, Suite 501, Mississauga, Ontario L4W 4Y1 Tel: +1 905 602-6222
Fax: +1 905 602-6221

The manufacturer reserves the right to change the specification without notice.

All trademarks are courtesy of registered owners. The DM logo is a trademark of Dedicated Microcomputers Group Ltd.

MKT-SD-D-002E Rev. 05/08

www.dedicatedmicrosinc.com

