

# STANDALONE DVR SYSTEM



## DV100S



FRONT



BACK



### SPECIFICATION

ITEM	FEATURE	DESCRIPTION		
VIDEO INPUT	CHANNEL SIGNAL FORMAT SIGNAL FORMAT SELECTION VIDEO LOSS CHECK	1 CH NTSC/PAL Composite S/W user selection YES		
VIDEO OUTPUT	CHANNEL SIGNAL FORMAT SIGNAL FORMAT SELECTION	DISPLAY OUTPUT 1 CH NTSC/PAL S/W selection	VGA OUTPUT NO	
ALARM INPUT	INPUT CHANNEL CONTACT FORM	1 Dry Contact, NC/NO selectable		
ALARM OUTPUT	OUTPUT CHANNEL CONTACT FORM	1 Relay, NC/NO selectable		
RECORDING	COMPRESSION MULTIPLEX RECORDING TYPE  RESOLUTION FRAME RATE FRAME RATE SELECTION  IMAGE SIZE  RECORDING METHOD  PREALARM	M-JPEG Simplex Full Screen Recording  NTSC 720(H) x 480(V) 30FPS NTSC - 30, 15, 10, 6, 5, 3, 2, 1, 0.5, 0.25, 0.2, 0.1 PAL 720(H) x 576(V) 25FPS PAL - 25, 12.5, 8.3, 5, 4.2, 1.7, 1, 0.5, 0.25, 0.2, 0.1  BEST 40K  Continuous Record Mode Schedule Record Mode Event Record Mode  YES		
DISPLAY	HDD FULL WARNING FRMAE RATE	YES NTSC 30 FPS	PAL 25 FPS	
SEARCH	PLAYBACK SPEED	PLAY x 1, 1/2, 1/4, 1/8	FAST FORWARD x 2, 4, 8	FAST REVERSE -1, 2, 4, 8
STORAGE	INTERANL HDD	INTERFACE TYPE EIDE/ATA133 Interface	HDD QUANTITY 1 HDD	
AUTHORIZATION	PASSWORD PASSWORD CHARACTER LENGTH DEFAULT PASSWORD	Software System Password 8 digits nothing		
CASE	DIMENSION - REMOVABLE TYPE	253(W) x 255(D) x 80(H)mm		
ADDITIONAL FUNCTION	EXTERNAL MULTIPLEXER SUPPORT MOTIONDETECTION SNAPSHOT	YES YES Image Capture through Serial Port		