

STANDALONE DVR SYSTEM



DV400D



FRONT



BACK

SPECIFICATION

ITEM	FEATURE		SPECIFICATION	
VIDEO	INPUT CHANNEL		4CH, Composite, 1Vp-p, 75Ω	
	DISPLAY OUTPUT		1 CH, Composite, 1Vp-p, 75Ω	
	PASS OUT		Loop Through 4ch(Rack Type)	
	DISPLAY RATE	NTSC 30 FPS / Channel	PAL 25 FPS / Channel	
	DISPLAY RESOLUTION	720(H) x 480(V) (NTSC)/ 720(H) x 576(V) (PAL)		
AUDIO	INPUT CHANNEL		4CH, RCA	
	OUTPUT CHANNEL		1CH, RCA	
ALARM	INPUT	CHANNEL 4CH	CONTACT FORM TTL IN, Normal Open/Normal Close Selectable.	
	OUTPUT	CHANNEL 2CH	CONTACT FORM RELAY OUT	
STORAGE	INTERNAL HDD	INTERFACE TYPE	EIDE/ATA Interface	
		Optional	80GB Removable(Portable type)	
	Optional	Can add another HDD (Rack type)		
	SUPPORTING BACKUP DEVICE	Network Connection	Client Computer back-up by Ethernet	
OPERATING SYSTEM			RTOS	
RECORDING	COMPRESSION		MPEG1/MPEG2 Hardware CODEC	
	RECORDING TYPE		4ch switching Recording	
	FRAME RATE SELECTION	NTSC	1,2,3,5,6,10,15,30(frame/sec)	
		PAL	1.0,1.7,2.5,4.2,5.0,8.3,12.5,25(frame/sec)	
	FRAME SIZE	HIGH	24.0k(Mpeg2), 10.5k(Mpeg1)	
		MEDIUM	20.7k(Mpeg2), 9.0k(Mpeg1)	
		LOW	17.3k(Mpeg2), 7.3k(Mpeg1)	
RECORDING MODE	CONTINUOUS RECORDING	Continuous Record Mode		
	TIMER RECORDING	Schedule Record Mode		
	SCHEDULE RECORDING	Schedule Record Mode		
	EVENT RECORDING	Event Record Mode		
	HDD Write Duration at Continuous Recording Mode		Indicate 0% ~ 99%	
	VIDEO LOSS CHECK		Display Video Loss Alarm, Send Video Loss event with LAN	
SEARCH	PLAYBACK SPEED	PLAY 1X	FAST FORWARD 2X, 4X, 8X, 16X	
		FAST REVERSE 2X, 4X, 8X, 16X		
AUTHORIZATION	USER LEVEL	USER SUPERVISOR	N/A System Password	
	PASSWORD CHARACTER LENGTH		4 numbers	
	DEFAULT PASSWORD		None	
REMOTE ACCESS	PROTOCOL		TCP/IP	
	REMOTE LIVE		Live display	
	REMOTE SEARCH		Remote Play back	
	REMOTE BACKUP		Download File (with JPG, MPG)	
	REMOTE SETUP		Can be with serial(optional)	
CASE	DIMENSION	REMOVABLE TYPE	253(W)×315(D)×80(H)mm	
		RACK TYPE	430(W)×348(D)×44(H)mm	
REAR PANEL	VIDEO I/O	4 IN/ 1OUT	BNC	
	AUDIO I/O	1OUT/ 4IN	RCA	
	ETHERNET PORT	LAN	RJ45 Modular Jack	
	SENSOR INPUT PORT		Terminal Block	
	RELAY OUTPUT PORT		Terminal Block	
	MAIN POWER SWITCH		Toggle Switch	
	AC POWER CONNECTOR		100 VAC~240VAC(50Hz/60Hz)	
SPECIAL FUNCTION	Motion Detection			